

MEGA CRACK FILL

Elastic Crack Putty Based On Acrylic Emulsion

DESCRIPTION

- *MEGA CRACK FILL* is an one component elastic putty, ready to use, based on acrylic emulsion and special additives.

ADVANTAGES

- * One component ready to use, easy to apply
- * Has an excellent adhesion to joint sides for concrete, bricks, steel, wood, etc..
- * Flexible, weather resistant and fast drying
- * Receives all finishing putty and paints

FIELDS OF APPLICATIONS

- Filling cracks in building elements for exterior and interior uses.
- Filling joints between aluminum, wooden windows, doors and plaster

DIRECTION FOR USE

- Cracks should be thoroughly cleaned from dust, grease, laitance, oils and loose materials
- Cracks should be filled with *MEGA CRACK FILL* using a trowel
- In case of narrow and hair cracks, it is advisable to widen them till about 3 mm on a V shape
- For wide cracks, refill the crack with *MEGA CRACK FILL* after 12 hours

TECHNICAL INFORMATION

Density at 25° C	1.54 ± 0.01 kg/L	Solid Content	80 ± 2 %
Appearance	Putty	pH Value	8.5 – 10
Color	White	Initial Setting Time	1 hour at 25° C

STRENGTH in Construction

CONSUMPTION

1.5 kg / L

PACKAGES

1 kg, 5 kg, 15 kg

STORAGE

9 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.