

## MEGA CEMENT STRIP

Concrete Remover – Cleaning And Etching Compound

### DESCRIPTION

- \* **MEGA CEMENT STRIP** solvent for dissolving soild concrete and rust .
- \* Suitable for etching of concrete floors and surfaces prior to application of resin or other surfac coating.

### ADVANTAGES

- \* It dissolve concrete without the need for any manual cleaning and so eliminate damage to machinery and equipment .
- \* It dissolve the heaviest rust from equipment while good varnish remains unaffected .  
In cases where paint is under rusted or weather – worm , this paint will be suitably dissolved too .
- \* It generates a phoshpate coating on cleaned material which gives temporary rust protection when stored weather – sheltered .
- \* No corrosive action with glass , plastic, rubber and most base metals .
- \* Rapid concrete etching action.

### DIRECTIONS OF USE

#### 1- Cleaning of small tools

- Dilute the highly concentrated **MEGA CEMENT STRIP** with water ( 1:5 –1:10).
- Immerse each piece of equipment in the diluted **MEGA CEMENT STRIP** .
- Take the pieces completely clean after 30 minutes to 4 hours ( depending on kind and size of the soild concrete ) .

#### 2- Cleaning large item of equipment

- e.g. Readymix Trucks . Concrete Mixers or Barrows .
- **MEGA CEMENT STRIP** should be liberally applied to the deposits by a soft broom and allowed to soak overnight if possible .if the surfaces of the deposit can be cracked by mechanical means this will speed up the operation . In severe cases more than one application may be necessary . On completion of dissolved deposits and loose materials, they should be brushed and washed away with clean water .

#### 3- Etching concrete floors

- For etching surfaces to remove laitence and give mechanical key before applying resin or other coating  
**MEGA CEMENT STRIP** should be diluted with water and applied at the rater of approximately , 1 litre per 2 sq. meters The dilution will depend on the condition of the floors and the degree of etching required but normally it will be between 1:2and 1:4 when the action has finished, wash down thoroughly with clean water

#### STRENGTH in Construction

**PRECAUTIONS**

\* **MEGA CEMENT STRIP** is acid – based and should be and should be handled with care. It attacks zinc, aluminum and putty. In doubt about its effect on a material, test a small area before general application.

**HEALTH AND SAFETY**

Avoid contact with skin .Rubber gloves and goggles should be worn .Wash spillages with plenty of water .Enclosed areas should be well ventilated .If contact with eyes occurs , wash immediately with water and seek medical advise .

**TECHNICAL INFORMATION**

Density at 25 °C	1.47 ± 0.05 kg /l	Solids content	65 %
------------------	-------------------	----------------	------

**PACKAGE**

20 kg , 200 kg

**STORAGE**

1 year in sealed packs, under suitable storage conditions .

**TECHNICAL SERVICES**

For further information, on-site assistance and trails, Please contact our technical advisory services.

**STRENGTH in Construction**