

MEGA FORM

Chemical Mould Release Agent

DESCRIPTION

MEGA FORM is a specially formulated blend of mineral oils and selected additives.

ADVANTAGES

- * Minimizes surface blemishes and staining, promoting high quality fair – faced concrete
- * Reduces probability of damage to formwork extending its usable life
- * Ensures easy release of formwork
- * Minimizes cleaning of formwork before re-use
- * Suitable for use with all types of formwork

DIRECTION OF USE

- * For new shuttering no preparation of the surface is necessary .
- * Ensure that shutters are clean before application .
- * For used shuttering , all traces of cement and previously used form oils must be removed .
- * **MEGA FORM** is applied by brush, roller=, sprayer or sponge in the form of uniform thin coating prior to concreting
- * On metal,glass-fiber or any other imprevious surface,one coat of **MEGA FORM** is sufficient .
On new plain timber surfaces a further coat of **MEGA FORM**, should be applied before placing concrete .

TECHNICAL INFORMATION

Density at 25 °C	0.9 kg/l	Color	Transparent yellow
Flash Point	Over 64 ° C	Freezing Point	- 10 ° C

STRENGTH in Construction

CONSUMPTION

- By spray on metal surface or coated timber 45- 60 sq.m \ liter
- On timber 15 – 35 sq.m\ liter

PACKAGES

- 180 KG
- 20 KG

STORAGE

1 year in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.