

MEGA DRY PUTTY

Cement Base, Ready to Use Wall Putty

DESCRIPTION

* **MEGA DRY PUTTY** is a cementitious powder modified with specially formulated synthetic resins, and fillers for smoothing plasters.

ADVANTAGES

- Ready to use, easy to apply, just add water.
- Bonds strongly to all suitable surfaces such as: exposed concrete, precast elements, lime plaster surfaces, gypsum boards, rough bricks, and other substrates
- Weather resistant
- Suitable for interior and exterior applications
- Repairs cracks and holes in walls and ceilings

FIELDS OF APPLICATIONS

- * **MEGA DRY PUTTY** is used for smoothing and leveling plasters on different substrates.
- * For repairing cracks and small holes in walls and ceilings
- * Is suitable for interior and exterior applications and on damp or dry surfaces.
- * Can be coated with any type of paint

DIRECTION OF USE

- The surface, but must be free from dust, oil, grease, paints coating, etc.
- Mix **MEGA DRY PUTTY** with water with a ratio of 1 water : 3 powder and mix thoroughly.
- Apply on cement plaster or concrete using a trowel and smoothing the applied surface to create a uniform thickness
- Clean tools directly after use using water.

STRENGTH in Construction

TECHNICAL INFORMATION

Density at 25° C	1.15 ± 0.02 kg/l	Pot life at 25° C	Approx. 90 minutes
Appearance	White Powder or Grey	Rate of consumption	400-600 gm/m ² /coat

PACKAGES

25 kg

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.