

MEGA COAT

High Quality Plastic Emulsion Paint .

DESCRIPTION

*MEGA COAT acrylic base emulsion paint for interior and exterior uses complies with ESS 1539 -1993.

ADVANTAGES

- * Washable and good abrasion resistant
- * Resists the effect of moisture , U.V. rays and atmospheric conditions .
- * Suitable for all kind of plaster , concrete, bricks, wood , gypsum board , old plastic.
- * High hiding power with low consumption rate.
- * Fast drying , flat , white color resists yellowing .

METHOD OF APPLICATION

- Substrate should be clean , free of dust , oils , etc.
- To be mixed thoroughly before use
- Under coats to be diluted 35 % - 40 % with water .
- Finish coat to be diluted 5 % - 10 % with water .
- Apply necessary putty for leveling and smoothing between coats using MEGA PASTE.
- Can be applied by brush roller or sprayer .
- Drying time for re-coating 2 - 4 hours .

TECHNICAL INFORMATION

Density at 25° C	1.40 ± 0.03 kg\ l	Appearance	Flat white and colored to suit all tastes
Viscosity at 25° C	15 - 20 poise	Touch dry	30 - 45 min.
pH	7.5 - 8.5	Recoat	2-4 hours

STRENGTH in Construction

CONSUMPTION

1 kg covers 5 - 7 sq. m per coat

PACKAGES

5, 15 , 20 kg packs

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.