

MEGA LUX SUPER

High Quality Emulsion Paint For Exterior And Interior

DESCRIPTION

• MEGA LUX SUPER polyvinyl acrylic base emulsion paint for exterior and interior use

ADVANTAGES

- * Very high hiding power due to high percentage of very good quality titanium dioxide.
- * Good abrasion resistant .high washability.
- * Good adhesion to all kind of substrate such as plaster ,concrete , wood , gypsum board ,old plastic, alyked paint etc.
- * Resists the effect of U.V. rays, atmospheric condition.
- * MEGA LUX SUPER is durable, flexible for all kind of surfaces.
- * Very high hiding power with low consumption rate .
- * Fast drying ,flat ,white color resists yellowing .

METHOD OF APPLICATION

- * Substrate should be clean, free of dust, oils, etc..
- * To be mixed thoroughly before use
- * Under coats to be diluted 20 % 30 % with water.
- * For best results apply 2 coats of MEGA LUX SUPER.
- * Apply necessary putty **MEGA PASTE** for leveling and smoothing between coats .
- * Can be applied by brush roller or sprayer.
- * Drying time for re-coating 2 4 hours.

TECHNICAL INFORMATION

Density at 25 °C	1.30 ± 0.03 kg/l	Appearance	White and colored
Touch dry	30 minutes	рН	7.5 – 8.5



CONSUMPTION

1 kg covers 7 - 9 sq.m per coat

PACKAGES

5, 15, 20 kg packs

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.