

MEGA TRAFFIC PAINT

Alkyd Special Paints For Marking Roads And Asphalt Flooring

DESCRIPTION

- * **MEGA TRAFFIC PAINT** is an one component, ready to apply paint, based on alkyd polymers, pigments and special filling materials which have high resistance to friction, atmospheric conditions, chemicals, water and fuel attack
- * **MEGA TRAFFIC PAINT** complies with ESS 794/1995

ADVANTAGES

- High resistant to friction
- Resistant to different weathering conditions
- Resistant to chemicals, fuels and water
- Can be applied on both concrete and asphalt flooring
- Can be used on wooden surfaces
- Economic and easy to use

FIELDS OF APPLICATIONS

Marking concrete and asphalt flooring of roads, high ways, parking areas, playgrounds and garages

DIRECTION FOR USE

- All surfaces to be coated should be free from dust, oils, grease, old paint and loose adhering deposits
- On newly constructed asphalt and concrete pavements, the surfaces must be allowed to dry
- Apply one coat or more according to the work requirement using brush, roller or spray
- Apply second coat depending upon the substrate conditions, the time between the two coats should be 4-5 hours
- The used tools should be cleaned with suitable solvent immediately after use

TECHNICAL INFORMATION

STRENGTH in Construction

Density at 25° C	1.38 ± 0.02 kg/l black 1.62 ± 0.02 kg/l white and yellow	Solid content	58 ± 1.0 %
Color	White-yellow-black	W.F.T	150-200 micron
Tack free on 25° C	15-30 minutes	Hard drying time at 25° C	2-3 hours
Rate of use	200-250 gm/m ² /coat	Abrasion Resistance	Not less than 1500 at 25° C

PACKAGES

18 kg, 5 kg

STORAGE

9 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.