

MEGA HARD WEATHER

High Quality Acrylic Paint

DESCRIPTION

* **MEGA HARD WEATHER** high quality , acrylic emulsion , semi – gloss latex paint for exterior use against severe weather conditions .

ADVANTAGES

- * **MEGA HARD WEATHER** for exterior and interior use .
- * Stable against U.V. rays , moisture and atmospheric conditions.
- * Durable , flexible , good wash ability and excellent adhesion for all kind of surfaces
- * Very high hiding power with low consumption rate.
- * Fast drying , flat , white color resists yellowing and does not change with time.

METHOD OF APPLICATIONS

- * Substrate should be clean , free of dust , oils , etc..
- * To be mixed thoroughly before use
- * Under coats to be diluted 15 % - 20 % with water .
- * For best results apply 2 coats of **MEGA HARD WEATHER** .
- * Apply necessary putty **MEGA PASTE** for leveling and smoothing between coats .
- * Can be applied by brush roller or sprayer .
- * Drying time for re-coating 2 - 4 hours .

PROPERTIES

Density at 25 °C	1.30 ± 0.01 kg/l	Appearance	Flat and Colored
Viscosity at 25 °C	15 – 20 poise	Application	Roller , Brush and Spray
Drying Time at 25°C	40-60 minutes	Solid Content	65 %
pH	7.5 – 8.5	Dry Film Thickness	100 microns

STRENGTH in Construction

CONSUMPTION

1 kg covers 7 - 9 sq.m per coat

PACKAGES

5, 15 , 20 kg packs

STORAGE

12 months in sealed packs , under suitable storage

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.