

MEGA FLOOR SEAL

Protective Coating For Concrete And Asphalt Floors

DESCRIPTION

- **MEGA FLOOR SEAL** is a non flammable one component, P.V.A emulsion base to be used as an anti- fuel and organic acids resistente.

ADVANTAGES

- * **MEGA FLOOR SEAL** provides a high resistant surface to final, diluted acids and heavy traffic loads.
- * High bonding stress to concrete and asphalt surface available in wide range of colours .

FIELD OF APPLICATIONS

- Asphalt or concrete floors subjected to petrol products as gasoline, diesel oil and grease.
- Warehousing and storage area.
- Garages and parking area.
- Factories.

METHOD OF APPLICATION

- The surface should be free from dust, oils, and grease, ect.
- Dilute **MEGA FLOOR SEAL** with water in the ratio of 1: 3 to obtain a primer coat.
- Apply a primer coat with roller.
- Apply a final coat without dilution and let to dry before use 48 hours at 20 ° C.

STRENGTH in Construction

TECHNICAL INFORMATION

Specific gravity at 25° C	1.5 kg /l	Touch dry	30 min.
Solid content	65 %	Viscosity at 25° C	35 seconds

CONSUMPTION

- Per coat 200 –300 gm / sq.m

PACKAGES

- 20 kg – 5 kg

STORAGE

6 months in sealed packs, under suitable storage conditions.

TECHNICAL SERVICES

For further information, on-site assistance and trails, Please contact our technical advisory services.